

1. Product Information					
1.1 Model Name/产品型号	YD25L-NW005-27AW-6N YD25L-NW005-30AW-6N YD25L-NW005-40AW-6N YD25L-NW005-65AW-6N	YD25L-NW005-40AW-6N- 镜面环	YD25L-AW005-27AW-6N YD25L-AW005-30AW-6N YD25L-AW005-40AW-6N YD25L-AW005-65AW-6N	YD25L-AW005-40AW-6N- 镜面环	YD25L-N0040-27AW YD25L-N0040-30AW YD25L-N0040-40AW
1.2 Render/Product Photo					
1.3 Electrical Class	Class II	Class II	Class II	Class II	Class II
1.4 Dimmable (1-10V/DALI)	/	/	/	/	/
1.5 Emergency Function/应急功能	NA	NA	NA	NA	NA
1.6 IP	IP65	IP65	IP65	IP65	IP65
1.7 IK	IK03	IK03	IK03	IK03	IK03
2. Complete Product Electrical Data/电参数					
2.1 Input Voltage (V)	AC230V	AC230V	AC230V	AC230V	AC120V
2.2 Input Current (A)	0.055	0.055	0.03	0.03	0.07
2.3 Rated Frequency (Hz)	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
2.4 Total Power (W)	5W	5W	5.5W	5.5W	4.8W
2.5 Power Factor	0.5	0.5	0.9	0.9	0.5
2.6 Output Voltage of Driver (V)	260	260	256	256	128
2.7 Output Current of Driver (mA)	15	15	15	15	28
2.8 Standby Power/待机功耗 (W)	/	/	/	/	/
2.9 Start Time/启动时间 (S)	<0.5	<0.5	<0.5	<0.5	<0.5
2.10 Output ripple curren/输出纹波电流 (%)	<20%	<20%	<20%	<20%	<20%
2.11 Flickering Percentage /频闪 (%)	svm<0.4	svm<0.4	svm<0.4	svm<0.4	svm<0.4
2.12 Total Harmonic Distortion (THD) (%)	<130%	<130%	<30%	<30%	/
2.13 Inrush Current/冲击电流 (A)	/	/	/	/	/
2.14 Inrush Duration/冲击电流时间 (μs)	/	/	/	/	/
2.15 Surge voltage capability/浪涌 (V)	500	500	500	500	500
2.16 Noise level/噪音 (dB)	24	24	24	24	24
3. Photometric Data (光参数)					
3.1 Lumen Output (lm)	400 @4000K	360 @4000K	360 @4000K	345 @4000K	380 @4000K
3.2 Efficacy (lm/W)	80	72	72	70	75
3.3 CCT (K)	2700/3000/4000/6500K	2700/3000/4000/6500K	2700/3000/4000/6500K	2700/3000/4000/6500K	2700/3000/4000
3.4 CRI	80	80	80	80	80
3.5 SDCM	<6	<6	<6	<6	<6

3.6 UGR	-	/	/	/	/	/
3.7 Beam Angle	(°)	100	100	100	100	100
3.8 Photometric View	-					
<b>4. Lifetime</b>						
4.1 Lifespan/寿命	(h)	15000	15000	15000	15000	15000
4.2 Warranty year/质保	-	3-year	3-year	3-year	3-year	3-year
4.3 Switching Cycle/开关次数	-	/	/	/	/	/
4.4 Ambient Temperature Range/环境温度	(°C)	-10°C to 40°C	-10°C to 40°C	-10°C to 40°C	-10°C to 40°C	-10°C to 40°C
<b>5. Mechanical and Housing</b>						
5.1 Housing Material/灯体材质	-	PA	PA	PA	PA	PA
5.2 Housing color/灯体颜色	-	white	white	white	white	white
5.3 Optical/Lens Material/光学材质	-	PC	PC	PC	PC	PC
5.4 Material of mounted ring /面环材料	-	/	/	/	/	/
5.5 Color of mounted ring /面环颜色	-	/	/	/	/	/
5.6 Glow wire test /灼热丝	(°C)	650	650	650	650	650
5.7 Installation method/安装方式	-					
5.8 Length	(mm)	ø87	ø89	ø87	ø89	ø87
5.9 Width	(mm)	/	/	/	/	/
5.10 Height	(mm)	35	37	35	37	35
5.11 Cut out	(mm)	ø68	ø68	ø68	ø68	ø68
5.12 Weight/重量	(KG)	0.043	0.054	0.043	0.054	0.043
5.13 Luminaire coverable/可覆盖	-	/	/	/	/	/
5.14 Drawing /Picture	-					